

Oyster3 LoRaWAN®

All 868, 902-928MHz LoRaWAN®
regions supported

Next generation of our best-selling Oyster series -
Ultra-rugged battery-powered GPS asset tracking
device for LoRaWAN® networks featuring 10 years
battery life (4x battery life of Oyster LoRaWAN)



'Deploy Once' Battery Life

Over 10+ years battery life on
user-replaceable 3 x AA Lithium
or Lithium Thionyl Chloride (LTC)
batteries for extreme temperature
operation

Adaptive Tracking

Periodic or optional movement-
based tracking - tracks assets
throughout the day and/or when
movement occurs, entering sleep
mode when inactive to conserve
power and data usage

Battery Life Monitoring

Periodic battery status uplinks give
a breakdown of power use

Ultra-Rugged

IP67 rated housing ensures
the device can withstand fine
dust, high-pressure spray, and
submersion for 30 minutes in 1m
of water

Connectivity

LoRaWAN	Highly sensitive radio transceiver is available in a single multiband device. Both 868 and 902 - 928 MHz supported
LoRaWAN Regions	AU915 AS923-1 AS923-2 AS923-3 AS923-4 EU868 IN865 KR920 RU864 US915

Batteries

User-Replaceable Batteries	3 x AA
Supported Battery Types	Alkaline *Lithium (LiFeS2) *Lithium Thionyl Chloride (LTC) *Lithium or LTC recommended for best performance. Please dispose of Lithium batteries in a safe and responsible manner.
Battery Life	Once Daily location updates – 10+ years Movement-Based location updates – 5 years Hourly location updates – 2 years

Location

GNSS Module	Sony CXD5605
Constellation	Concurrent GPS, GLONASS, Galileo, QZSS
Tracking Sensitivity	-147 dBm cold start / -161 dBm hot start
Low Noise Amplifier	GPS signals are filtered and boosted by a SAW filter and low-noise amplifier (LNA) allowing operation where other units fail
LoRaWAN Gateway Geolocation Fallback	LoRaWAN gateway geolocation fallback when there is no GNSS

Power

Input Voltage	4-15V DC
Sleep Current	<10uA* *Average current in lowest power configuration
Safety	Reverse Polarity Protection

Mechanics / Design

Dimensions	108 x 86 x 30 mm (4.25 x 3.39 x 1.18")
Weight	180g
Housing	Ultra-Rugged IP67 Housing. Non-branded housing for optional white-labeling.
IP Rating	IP67 rated housing ensures device can withstand fine dust, high-pressure spray, submersion for 30 mins in 1m of water, and extreme temperatures
Installation	Compact and concealable. Multiple installation options for covertly and easily securing the device to assets with screws, bolts, cable ties, rivets, and more. Stainless steel screws supplied.
Operating Temperature	-30°C to +60°C - for operation in extreme temperatures use LTC batteries
GPS Antenna	Internal
RF Antenna	Internal
3-Axis Accelerometer	3-Axis Accelerometer to detect movement
Diagnostic LED	Diagnostic LED indicates operation status
On-Board Speed & Heading	Current speed and heading is reported with each position update

Smarts

Battery Life Monitoring	Periodic battery status uplinks give a breakdown of power use
Geofence Alerts	The server can use device location to create geofences and alerts if an asset enters or leaves designated locations
Periodic or Movement-Based Tracking	Configure parameters to send updates based on set time intervals or when movement occurs. Adaptive tracking technology detects when the device is on the move and increases the update rate, providing detail when you need it while conserving battery when stationary.
Sleep Mode	Stationary devices enter sleep mode until movement occurs to conserve battery life and optimize data usage
Theft Recovery	Reduce or minimize asset loss and theft
Tip Detection and Rotation Counting	Axis angle reporting, tip detection and rotation counting (planned)

Device Management

Flexible Configuration	Configure device parameters such as position update rate, movement and accelerometer settings, and more to fit any tracking application
Configuration App	Manage device firmware updates and parameters via DMLink provisioning tool. Some parameters can be changed via downlink.

Integration

Third-Party Integration	Easy integration with comprehensive documentation and a flexible and open payload format
-------------------------	--

Security

Data Security	LoRaWAN® networks use AES-128 Encryption so your data is protected
---------------	--

Warranty

Manufacturer's Warranty	Two-year manufacturer's warranty
-------------------------	----------------------------------

Certifications

Please visit support.digitalmatter.com for a full list of compliance specifications and documentation for your region	FCC, ICASA, CE, UKCA, ACMA
---	----------------------------