

# Yabby3 LoRaWAN®

All 868, 902-928MHz LoRaWAN®  
regions supported

Ultra-rugged and compact battery-powered  
GPS asset tracking device for LoRaWAN®  
networks featuring 7 years battery life  
(4x battery life of previous generation)



## 'Deploy Once' Battery Life

Over 7+ years battery life on  
user-replaceable 3 x AAA Lithium  
batteries

## Adaptive Tracking

Tracks assets when they're on the  
move and enters sleep mode when  
stationary to conserve power

## Battery Life Monitoring

Periodic battery status uplinks give  
a breakdown of power use

## Ultra-Rugged

Ultra-rugged and weatherproof  
IP68, IK06 Housing

# Connectivity

---

LoRaWAN	Highly sensitive radio transceiver is available in a single multiband device. Both 868 and 902 - 928 MHz supported
---------	--

---

LoRaWAN Regions	AU915 AS923-1 AS923-2 AS923-3 AS923-4 EU868 IN865 KR920 RU864 US915
-----------------	--

---

# Batteries

---

User-Replaceable Batteries	3 x AAA. <i>Batteries not included.</i>
----------------------------	---

---

Supported Battery Types	Alkaline *Lithium (LiFeS2) - recommended for best performance.  *Please dispose of Lithium batteries in a safe and responsible manner.
-------------------------	---

---

**Battery Life Estimates	Once Daily location updates – 7 years Movement-Based location updates – 2 years Hourly location updates – 7 months
--------------------------	--

---

# Location

---

GNSS Module	Sony CXD5612
-------------	--------------

---

Constellation	Concurrent GPS, GLONASS, Galileo, BeiDou QZSS
---------------	---

---

Tracking Sensitivity	-147dBm cold start / -161dBm hot start
----------------------	--

---

*Location Accuracy	~1m 2D RMS, GPS, -130dBm
--------------------	--------------------------

---

Low Noise Amplifier	GPS signals are filtered and boosted by a SAW filter and low-noise amplifier (LNA) allowing operation where other units fail
---------------------	--

---

LoRaWAN Gateway Geolocation	LoRaWAN gateway geolocation fallback when there is no GNSS (Network Specific)
-----------------------------	---

---

# Power

---

Input Voltage	4-5.5 VDC
---------------	-----------

---

Sleep Current	<1.5uA* *Average current in lowest power configuration
---------------	---

---

## Mechanics / Design

Dimensions	Standard - 84 x 63 x 24 mm (3.31 x 2.48 x 0.94") Livestock Collar - 109 x 60 x 30 mm (4.29 x 2.36 x 1.18") Snap Housing (Smallest Size, not IP rated) - 75 x 45 x 25 mm (2.95 x 1.77 x 0.98")
Weight	TBD
Housing	Non-branded housing for optional white-labeling
IP/IK Rating	Ultra-rugged and waterproof IP68 and IK06-rated housing ensures the Yabby3 LoRaWAN can withstand impact, fine dust, and brief submersion
Installation	Compact and concealable. Multiple installation options for covertly and easily securing the device to assets with screws, bolts, cable ties, rivets, and more. Stainless steel screws supplied.
Operating Temperature	-30°C to +60°C
GPS Antenna	Internal
RF Antenna	Internal
3-Axis Accelerometer	3-Axis Accelerometer to detect movement
Diagnostic LED	Diagnostic LED indicates operation status
On-Board Speed & Heading	Current speed and heading is reported with each position update

## Smarts

Battery Life Monitoring	Periodic battery status uplinks give a breakdown of power use
Geofence Alerts	The server can use device location to create geofences and alerts if an asset enters or leaves designated locations
Periodic or Movement-Based Tracking	Configure parameters to send updates based on set time intervals or when movement occurs. Adaptive tracking technology detects when the device is on the move and increases the update rate, providing detail when you need it while conserving battery when stationary.
Sleep Mode	Stationary devices enter sleep mode until movement occurs to conserve battery life and optimize data usage
Theft Recovery	Reduce or minimize asset loss and theft

## Device Management

Flexible Configuration	Configure device parameters such as position update rate, movement and accelerometer settings, and more to fit any tracking application
Configuration App	Manage device firmware updates and parameters via DMLink provisioning tool. Some parameters can be changed via downlink.

# Integration

---

Third-Party Integration

Easy integration with comprehensive documentation and a flexible and open payload format

---

# Security

---

Data Security

LoRaWAN® networks use AES-128 Encryption so your data is protected

---

# Warranty

---

Manufacturer's Warranty

Two-year manufacturer's warranty

---

# Certifications

---

Please visit our knowledge base for a full list of compliance specifications and documentation for your region

Coming soon

---

\* Positioning accuracy specifications are provided by the GNSS supplier and reflect ideal conditions. Device configuration, installation, environmental conditions, augmentation services, and many other factors may lead to variations in positioning accuracy.

\*\*Battery life estimates are influenced by several factors including temperature, installation and orientation of the device, the frequency of location updates, network coverage, sensor integrations, peripherals, accelerometer settings, and more. Estimated battery life calculators are available at [support.digitalmatter.com](http://support.digitalmatter.com).